

SPECIFICATION SHEET

PCP

POWER CABLE PLOUGH

PCP-2 is a high performance power cable plough with the capability to operate around the world, providing the burial and immediate backfill of power cables. The Power Cable Plough is ideally suited to the Offshore Renewables market, providing the burial of inter-array and export cables.

With burial performance in a variety of soil conditions, the plough can support either simultaneous or post-lay operations. In certain seabed conditions, an enhanced burial performance is obtained through the utilisation of the 300kW water jetting system, which reduces tow forces and increases ploughing performance.



KEY FEATURES

- Self loads product subsea.
- 3.5m bend radius for products with high MBR.
- 300kW water jetting system reduces tow force.
- Trench depths up to 2.4m at current configuration.

ENSHORESUBSEA.COM

PCP

PARTICULARS	
Max. Operating Depth	1500 m
Max. Product Diameter	240 mm
Product MBR	3.5 m (Share and Depressor)
Mx. Trench Depth	Up to 2.4 m
Speed Range	Up to 1000 m / hr (Product Dependant)
Tow Force	130 Te
Length	12.25 m (with depressor fully down)
Width	6.3 m
Height	6.95 m (with drawbar raised) 4.7 m (with drawbar down)



WEIGHT

In Air	45 Te
In Water	40 Te

BURIAL TOOL	
Share Design	Parallel sided blade provides low pull force and good penetration in a variety of sands subject to there being adequate pull force.
Additional Tools	Water jetting system - 300 kW
Depth Control	Continuously variable between 0.73 m and 2.4 m using the front skids.

SOIL TYPE

Suitable for a range of soil types, including sands and very soft to hard clays.

SURVEILLANCE EQUIPMENT

- 6 x Explorer Pro CCD
- 1 x 1017 OA Sonar

6 x LED Lights with Dimming Capability

Provisions for $3 \times \text{Gemini} 720's$

Octans Gyro



ENSHORESUBSEA.COM